



Mounted Disc Plough MF Type

Mounted Disc Plough can handle the toughest ploughing jobs. For extremely hard ground and soil with large roots and other obstructions, one can obtain outstanding penetration performance. For soft sticky ground and sandy soil, depth can be controlled through the built-in depth control. The under frame and unit-to-unit clearances are adequate to cope with trashy conditions. Perfect alignment of the sub-beams carrying the Disc bottoms is maintained by virtue of the frame construction. An adjustable and spring-loaded furrow wheel takes care of the side draft and the implement moves smoothly. Disc tilt angle can be varied in three stages to perform on various types of soils.

Technical Specifications (Item Code:GK11)

	2 Bottom	3 Bottom	4 Bottom	5 Bottom
Tractor Power (HP)	50-60	65-75	75-90	100-125
Frame	Seamless Tubular Frame	Seamless Tubular Frame	Seamless Tubular Frame	Seamless Tubular Frame
Length	1800 mm	2400 mm	3000 mm	3600 mm
Mounted CAT.	CAT-II	CAT-II	CAT-II	CAT-II/CAT-III
Discs	660X6T mm(26")	660X6T mm(26")	660X6T mm(26")	660X6T mm(26")
Bearing Hubs	2	3	4	5
Weight	310 Kg (Approx.)	415 Kg (Approx.)	510 Kg (Approx.)	620 Kg (Approx.)